

Product Specification



Product Title: FIBROUS NO 4 CLR HP-L CUT & TIED 50CM

Product Code: TFHPL04A50SD

1 Product Specification :

1.1 Fibrous

2 Product Description :

2.1 Fibrous casing is manufactured using Good Manufacturing Practice (GMP).
It is available in a variety of sizes, types, and colors to suit any application.

3 Sales Unit :

3.1 Fibrous casings can be delivered in flat pieces, pretied pieces, bundles, reels or shirred strands.
(For information, please visit VT website at : www.viskoteepak.com)

4 Base Stock Product Composition (Typical Analysis) :

4.1	Cellulose	:	75 + - 2 %
4.2	Plasticizer	:	20 + - 2 %
4.3	Water	:	4 + - 2 %
4.4	Colors	:	< 1% (Colored and printed casings only)

5 Physical Attributes :

5.1	Caliber	:	75
5.2	Recommended Stuffing Caliber	:	84
5.3	Horn	:	48
5.4	Soaking time	:	Minimum 30 minutes

6 Converting Issues

6.1	Length (cm)	:	50
6.2	Pieces per bundle	:	25
6.3	Pieces per carton	:	500
6.4	Presticking	:	No
6.5	Drilled	:	No
6.6	Clipped	:	No
6.7	Pretied	:	Yes
6.8	Loop color	:	White

While we have taken all reasonable steps to verify the accuracy of the information contained in this specification, no warranties are given to this effect and purchasers should determine for themselves whether products are suitable for their own specific use. The information contained in this specification is intended for the customer it has been issued to. It must not be reproduced, or the information contained therein passed on to any third party without the written consent of Scobie & Junor.

Product Specification



7 Product Microbiological Condition :

7.1 Our products are routinely checked for microbiological contamination

8 Product Identification :

8.1 Carton : Type - Code - Caliber - Order number

9 Product use :

- 9.1 Storage condition : Casings have to be stored under dry and cool conditions at normal warehouse temperature of 5 - 25 centigrade, for granted shelflife of 24 months after production date.
Opened cartons have to be properly reclosed to avoid drying out.
- 9.2 User recommendation : Casings have to be pre-soaked at an optimal temperature of 30 - 40 centigrade for at least 30 minutes before stuffing. Once casings have been soaked, they have to be used up within max. 24 hours.
- 9.3 Application : Dry sausages - Semi-dry sausages - cooked sausages - smoked applications

Cellulose casings do not contain genetically modified organisms (GMOs). GMOs are not used during the manufacturing.
Cellulose casings do not contain the substances or products causing allergies or intolerances as listed in Regulation (EU) No 1169/2011 Annex II.

Customer Approval of Specification		
Please sign and return this specification to technical@scobie-junor.co.uk to confirm formal acceptance of this specification. All specifications issued will be deemed to be accepted if no communication to the contrary is received after 10 working days.		
Signature:		
Print name:		
Position:		
Date:		

Issued by Scobie & Junor (Estd. 1919) Ltd. Certified accurate on 23/05/2022 10:08:11

While we have taken all reasonable steps to verify the accuracy of the information contained in this specification, no warranties are given to this effect and purchasers should determine for themselves whether products are suitable for their own specific use. The information contained in this specification is intended for the customer it has been issued to. It must not be reproduced, or the information contained therein passed on to any third party without the written consent of Scobie & Junor.